

Rondomat - the ergonomic dough sheeter

The reliable Rondomat features ergonomic design and is particularly easy to clean.



SSO 6404



SSO 6407
with the options: flour catch pans,
plastic conveyor belts

Technical Data

Rondomat	SSO 6404	SSO 6405	SSO 6407
Substructure A-frame	in stainless steel	in stainless steel	in stainless steel
Automatic flour duster	optional	optional	optional
Width of conveyor belts	640 mm	640 mm	640 mm
Table length overall	2300 mm	2730 mm	3330 mm
Roller length	660 mm	660 mm	660 mm
Roller gap	0.3 - 45 mm	0.3 - 45 mm	0.3 - 45 mm
Roller gap reduction	manual	manual	manual
Speed of discharge conveyor	80 cm/s	80 cm/s	80 cm/s
Rated power	2.0 kVA / 1.1 kW	2.0 kVA / 1.1 kW	2.0 kVA / 1.1 kW
Supply voltage	3 x 200 - 460 V, 50/60 Hz	3 x 200 - 460 V, 50/60 Hz	3 x 200 - 460 V, 50/60 Hz
Required floor space (mm)			
• in working position, catch pans extended	1330 x 2670 mm	1330 x 3100 mm	1330 x 3620 mm
• in resting position	1330 x 1550 mm	1330 x 1815 mm	1330 x 2180 mm
Weight	260 kg	270 kg	275 kg

The right to make changes of a technical nature is reserved. The technical safety and type-specific instructions in the operating manual must be complied with. Prohibition, information and warning signs on the machines are to be complied with in accordance with the operating instructions.

